

# FASTCOOL

Evaporative Air Cooler Specialist

## Contact Us

### DENSBE ELECTRICAL S'pore Pte

403 RACE COURSE ROAD SINGAPORE  
218653  
Tel: (65) 6447 3744  
Fax: (65) 6344 1254  
Email: [sales@densbe-electric.com](mailto:sales@densbe-electric.com)  
[densbe@singnet.com.sg](mailto:densbe@singnet.com.sg)  
Website: [www.densbe-electric.com](http://www.densbe-electric.com)



Professional Evaporative Air Cooler

## DLB008-EQ

|                                   |                              |
|-----------------------------------|------------------------------|
| Model                             | DLB008-EQ                    |
| Airflow (m3/h)                    | 800                          |
| Volt/freq. (V/Hz)                 | 220/50                       |
| Power (W)                         | 90                           |
| Applicable Area (m <sup>2</sup> ) | 15-20                        |
| Fan Type                          | Cross Flow                   |
| Fan speed                         | 3                            |
| Control type                      | Mechanical                   |
| Product size                      | 30*28*66 cm or<br>30*28*81cm |
| Water tank (L)                    | 8 or 20                      |
| Gross weight (KG)                 | 6.9 or 8.2                   |
| Loading Q'ty (40 HQ)              | 990 pcs or 780 pcs           |

100% copper wire fan motor  
Easy to add water  
Cross flow fan with low noise design  
With ionizer to create fresh air



8L water tank

20L water tank

## DLB025-EQ2

|                 |                                 |
|-----------------|---------------------------------|
| Airflow         | 2500m3/h                        |
| Volt/Freq.      | 220V/50Hz                       |
| Power           | 85W                             |
| Fan type        | Axial fan                       |
| Fan speed       | 4 speeds                        |
| Control type    | LED display & remote controller |
| Water tank      | 13L                             |
| Applicable area | 15-25m3                         |
| N.W./G.W.       | 6.4 / 7.5kgs                    |
| Product size    | 315*280*980mm                   |
| Packing size    | 361*326*1032mm                  |
| 40'HQ           | 610pcs                          |

New HPIS cooler body, durable and beautiful  
Motor with 100% copper coil  
Axial fan ensure 5-7m long air delivery  
**4 side cooling pad**  
Water shortage warning and protection  
Auto swing from left to right



4 pcs of thick 9050 cooling pads



Easy for adding water from top

## DLBO25-EQ

|                 |                                 |
|-----------------|---------------------------------|
| Airflow         | 2500m <sup>3</sup> /h           |
| Volt/Freq.      | 220V / 50Hz                     |
| Power           | 100W                            |
| Fan type        | Centrifugal                     |
| Fan speed       | 3 speeds                        |
| Control type    | LED display & remote controller |
| Water tank      | 15L                             |
| Applicable area | 15-25m <sup>2</sup>             |
| N.W./G.W.       | 10 / 12 Kgs                     |
| Product size    | 33 × 35 × 89 cm                 |
| Packing size    | 36 × 38 × 93 cm                 |
| 20'GP / 40'HQ   | 225 / 510 pcs                   |

New ABS cooler body, durable and beautiful  
 100% copper-wire winding motor  
 Centrifugal fan ensures 5-7m long air delivery  
**4 side cooling pad**  
 Water shortage warning and protection  
 Auto swing from left to right



Detachable water tank, easy for cleaning



Easy for adding ice from top

## DLBO3-EQ2

|                 |                                 |
|-----------------|---------------------------------|
| Airflow         | 3000m <sup>3</sup> /h           |
| Volt/Freq.      | 220V / 50Hz                     |
| Power           | 120W                            |
| Fan type        | Axial                           |
| Fan speed       | 3 speeds                        |
| Control type    | LED display & remote controller |
| Water tank      | 35L                             |
| Applicable area | 20-30m <sup>2</sup>             |
| N.W./G.W.       | 11.4 / 13.5 Kgs                 |
| Product size    | 48x35x93cm                      |
| Packing size    | 52x39x99cm                      |
| 20'GP / 40'HQ   | 130 / 330 pcs                   |

New ABS cooler body, durable and beautiful  
 100% copper-wire winding motor  
 3 side cooling pad  
 Water shortage warning and protection  
 Auto swing from left to right  
**Easy for adding ice from top**



Rear side view  
 3 side big size cooling pad



With wide top open, easy to add ice



Control panel and  
 colored LED display

# DLBO4-EQ2

|                 |                                 |
|-----------------|---------------------------------|
| Airflow         | 4500m³/h                        |
| Volt/Freq.      | 220V / 50Hz                     |
| Power           | 110W                            |
| Fan type        | Axial                           |
| Fan speed       | 3 speeds                        |
| Control type    | LED display & remote controller |
| Water tank      | 45L                             |
| Applicable area | 35-50m²                         |
| N.W./G.W.       | 17.5 / 20.5 Kgs                 |
| Product size    | 51x42x120 cm                    |
| Packing size    | 55x47x123 cm                    |
| 20'GP / 40'HQ   | 97 / 236 pcs                    |

New PP cooler body, durable and beautiful  
 100% copper-wire winding motor  
 3 side cooling pad  
 Water shortage warning and protection  
 Auto swing from left to right  
**Easy for adding ice from top**



Front view



Back view



Detachable water tank, easy for cleaning



With wide top open, easy to add ice



Add water manually



3 pcs of thick 5090 cooling pads

# DLBO4-EQ

|                      |                     |
|----------------------|---------------------|
| Model                | DLB04-EQ            |
| Airflow (m3/h)       | 4000                |
| Volt/freq. (V/Hz)    | 220/50              |
| Power (W)            | 160                 |
| Fan speed            | 4                   |
| Fan type             | Axial, 2 Fans       |
| Noise (db)           | ≤59                 |
| Control type         | Electronic & Remote |
| Cooler size (mm)     | 420*320*1225        |
| Water tank (L)       | 32                  |
| Gross weight (KG)    | 12.9                |
| Loading Q'ty (40 HQ) | 340 pcs             |

Unique design with 2 fans to get a better airflow  
 4 fan speeds available  
 Turbo mode to get a strong airflow  
 3 pcs of high density 5090 cooling pads  
 With ice bag for a faster cooling  
 Electronic & Mechanical control optional



## DLB05-EQ2

|                                   |                                 |
|-----------------------------------|---------------------------------|
| Model                             | DLB05-EQ2                       |
| Airflow (m <sup>3</sup> /h)       | 5000                            |
| Volt/freq. (V/Hz)                 | 220/50                          |
| Power (W)                         | 180W                            |
| Applicable Area (m <sup>2</sup> ) | 35-50                           |
| Fan type                          | Axial                           |
| Fan speed                         | 3                               |
| Control type                      | Mechanical or Electronic&Remote |
| Product size (mm)                 | 620*400*1050                    |
| Packing size (mm)                 | 630*420*1030                    |
| Water tank (L)                    | 45                              |
| Gross weight (KG)                 | 17.5                            |
| Loading Q'ty (40 HQ)              | 236 pcs                         |

Big airflow and long drive distance  
 3 pieces of environmental friendly cooling pads  
 Cooling pads with high saturation rate up to 95%  
 100% copper wire fan motor  
 Mechanical or Electronic control optional



## DLB06-EQ

|                 |                                 |
|-----------------|---------------------------------|
| Airflow         | 6500m <sup>3</sup> /h           |
| Volt/Freq.      | 220V / 50Hz                     |
| Power           | 230W                            |
| Fan type        | Axial                           |
| Fan speed       | 3 speeds                        |
| Control type    | LED display & remote controller |
| Water tank      | 60L                             |
| Applicable area | 45-60m <sup>2</sup>             |
| N.W./G.W.       | 18.5 / 21.7 Kgs                 |
| Product size    | 72x43x122cm                     |
| Packing size    | 74x45x119cm                     |
| 20'GP / 40'HQ   | 72 / 176 pcs                    |

New PP cooler body, durable  
 100% copper-wire winding motor  
**3 side cooling pad**  
 Water shortage warning and protection  
 Auto swing from left to right



## DLB09-EQ / DLB12-EQ

|                 |                                 |
|-----------------|---------------------------------|
| Airflow         | 9000 m³/h / 12000 m³/h          |
| Volt/Freq.      | 220V / 50Hz                     |
| Power           | 350W / 420W                     |
| Fan type        | Axial                           |
| Fan speed       | 3 speeds                        |
| Control type    | LED display & remote controller |
| Water tank      | 100L                            |
| Applicable area | 50-100m²                        |
| N.W./G.W.       | 38 /42 KG                       |
| Product size    | 79*52*135cm                     |
| Packing size    | 85*55*132cm                     |
| 20'GP / 40'HQ   | 43/120 pcs                      |

New PP cooler body, durable  
 100% copper-wire winding motor  
**3 side cooling pad**  
 Large airflow, high performance-price ratio  
 Water shortage warning and protection  
 Auto swing from left to right



## DLB11-EQ

|                      |                     |
|----------------------|---------------------|
| Model                | DLB11-EQ            |
| Airflow (m3/h)       | 11000               |
| Volt/freq. (V/Hz)    | 220/50              |
| Power (W)            | 360                 |
| Fan speed            | 3                   |
| Fan type             | Axial, 2 Fans       |
| Noise (db)           | ≤59                 |
| Control type         | Electronic & Remote |
| Cooler size (mm)     | 590*415*1920        |
| Water tank (L)       | 70                  |
| Gross weight (KG)    | 39                  |
| Loading Q'ty (40 HQ) | 110 pcs             |

Unique design with 2 fans to get a better airflow  
 Up and down fans could be controlled independently  
 3 pcs of high density 5090 cooling pads  
 With full closed air diffusers to prevent dust  
 Electronic&Mechanical control optional



## DLB15-EQ

|                 |                                 |
|-----------------|---------------------------------|
| Airflow         | 15000m <sup>3</sup> /h          |
| Volt/Freq.      | 220V / 50Hz                     |
| Power           | 650W                            |
| Fan type        | Axial                           |
| Fan speed       | 3 speeds                        |
| Control type    | LED display & remote controller |
| Water tank      | 100L                            |
| Applicable area | 60-100m <sup>2</sup>            |
| N.W./G.W.       | 40 / 45 Kgs                     |
| Product size    | 87x57x140cm                     |
| Packing size    | 88x57x130 cm                    |
| 20'GP / 40'HQ   | 42 / 104 pcs                    |

New PP cooler body, durable  
 100% copper-wire winding motor  
**3 side cooling pad**  
 Large airflow, high performance-price ratio  
 Water shortage warning and protection  
 Auto swing from left to right



## DLB18-EQ

|                      |                     |
|----------------------|---------------------|
| Model                | DLB18-EQ            |
| Airflow (m3/h)       | 18000               |
| Volt/freq. (V/Hz)    | 220/50              |
| Power (W)            | 750                 |
| Fan speed            | 3                   |
| Fan type             | Axial               |
| Noise (db)           | ≤59                 |
| Control type         | Electronic & Remote |
| Cooler size (mm)     | 900*560*1450        |
| Water tank (L)       | 120                 |
| Gross weight (KG)    | 50                  |
| Loading Q'ty (40 HQ) | 94 pcs              |

Strong cabinet with fresh plastic material  
 Copper wire motor ensures long lifetime  
 3 pcs of high density 5090 cooling pads  
 Auto swing from left to right



## DLBW06-EQ

| Model                | DLBW06-EQ          |
|----------------------|--------------------|
| Airflow (m3/h)       | 6000               |
| Volt/freq. (V/Hz)    | 220/50             |
| Power/Current (Kw/A) | 200                |
| Fan Type             | Axial              |
| Fan speed            | 3                  |
| Control type         | Eletronic & remote |
| Noise (db)           | ≤62                |
| Air outlet size (mm) | 430*430            |
| Cooler size (mm)     | 640*640*700        |
| Water tank (L)       | 25                 |
| Gross weight (KG)    | 23                 |
| Loading Q'ty (40 HQ) | 215 pcs            |



Plastic case with fresh material, over 10 years lifetime  
 With full closed air diffuser to prevent dust  
 100% copper wire motor  
 3 pcs of high density 5090 cooling pads  
 With electronic & remote control



## DLBW08-EQ

| Model                | DLBW08-EQ          |
|----------------------|--------------------|
| Airflow (m3/h)       | 8000               |
| Volt/freq. (V/Hz)    | 220/50             |
| Power/Current (Kw/A) | 0.35KW / 1.6A      |
| Fan Type             | Axial              |
| Fan speed            | 3                  |
| Control type         | Eletronic & remote |
| Noise (db)           | ≤65                |
| Air outlet size (mm) | 628*678            |
| Cooler size (mm)     | 830*1065*800       |
| Water tank (L)       | 25                 |
| Gross weight (KG)    | 45                 |
| Loading Q'ty (40 HQ) | 144 pcs            |



Large airflow and long drive distance  
 High quality galvanized steel cabinet  
 100% copper wire fan motor  
 Auto drain function  
 Easy for installation



## DLBW10-EQ

|                      |                     |
|----------------------|---------------------|
| Model                | DLBW10-EQ           |
| Airflow (m3/h)       | 10000               |
| Volt/freq. (V/Hz)    | 220/50              |
| Power                | 420W                |
| Fan Type             | Axial               |
| Fan speed            | 4                   |
| Control type         | Electronic & remote |
| Noise (db)           | ≤65                 |
| Air outlet size (mm) | 628*678             |
| Cooler size (mm)     | 830*1145*800        |
| Water tank (L)       | 25                  |
| Gross weight (KG)    | 48                  |
| Loading Q'ty (40 HQ) | 130                 |



Large airflow and long drive distance  
High quality galvanized steel cabinet  
100% copper wire fan motor  
Auto drain function  
Easy for installation



## DLB18-DC



Save 30% energy by High efficiency BLDC motor  
Power consumption low to 780W  
Low noise design with motor 1400 RPM  
LCD display & Remote control  
Variable speed control  
Flame retardant and sealed PC box, waterproof  
Multiple safety protection

| Item No:                  | DLB18-DC            | DLB18-DC            |
|---------------------------|---------------------|---------------------|
| Air Discharge:            | Up                  | Up                  |
| Largest Airflow(m3/h):    | 18000               | 20000               |
| Voltage/Frequency(V/Hz):  | 220V/50Hz-60Hz      | 220V/50Hz-60Hz      |
| Power:                    | 780W                | 1000W               |
| Dimension L*W*H(mm):      | 1080*1080*980       | 1080*1080*980       |
| Fan Type:                 | Axial Fan,3-blade   | Axial Fan,3-blade   |
| Fan Speeds:               | 100 speeds inverter | 100 speeds inverter |
| Control Type:             | LCD panel & Remote  | LCD panel & Remote  |
| Water Capacity(L):        | 25                  | 25                  |
| Air Outlet Dimension(mm): | 670*670             | 670*670             |
| Applicable Area(m2):      | 100-150             | 100-150             |
| Gross weight (KG)         | 73                  | 73                  |
| 40'HQ                     | 95 pcs in SKD       | 95 pcs in SKD       |

## DLU18-DC



Save 30% energy by High efficiency BLDC motor  
 Power consumption low to 780W  
 Low noise design with motor 1400 RPM  
 LCD display & Remote control  
 Variable speed control  
 Flame retardant and sealed PCD box, waterproof  
 Multiple safety protection

| Item No:                  | DLU18-DC            | DLU20-DC            |
|---------------------------|---------------------|---------------------|
| Air Discharge:            | Up                  | Up                  |
| Largest Airflow(m3/h):    | 18000               | 20000               |
| Voltage/Frequency(V/Hz):  | 220V/50Hz-60Hz      | 220V/50Hz-60Hz      |
| Power:                    | 780W                | 1000W               |
| Dimension L*W*H(mm):      | 1080*1080*980       | 1080*1080*980       |
| Fan Type:                 | Axial Fan,3-blade   | Axial Fan,3-blade   |
| Fan Speeds:               | 100 speeds inverter | 100 speeds inverter |
| Control Type:             | LCD panel & Remote  | LCD panel & Remote  |
| Water Capacity(L):        | 25                  | 25                  |
| Air Outlet Dimension(mm): | 670*670             | 670*670             |
| Applicable Area(m2):      | 100-150             | 100-150             |
| Gross weight (KG)         | 75                  | 75                  |
| 40'HQ                     | 90 pcs in SKD       | 90 pcs in SKD       |

## DLD18-DC



Save 30% energy by High efficiency BLDC motor  
 Power consumption low to 780W  
 Low noise design with motor 1400 RPM  
 LCD display & Remote control  
 Variable speed control  
 Flame retardant and sealed PCD box, waterproof  
 Multiple safety protection

| Item No:                  | DLD18-DC            | DLD18-DC            |
|---------------------------|---------------------|---------------------|
| Air Discharge:            | Up                  | Up                  |
| Largest Airflow(m3/h):    | 18000               | 20000               |
| Voltage/Frequency(V/Hz):  | 220V/50Hz-60Hz      | 220V/50Hz-60Hz      |
| Power:                    | 780W                | 1000W               |
| Dimension L*W*H(mm):      | 1080*1080*980       | 1080*1080*980       |
| Fan Type:                 | Axial Fan,3-blade   | Axial Fan,3-blade   |
| Fan Speeds:               | 100 speeds inverter | 100 speeds inverter |
| Control Type:             | LCD panel & Remote  | LCD panel & Remote  |
| Water Capacity(L):        | 25                  | 25                  |
| Air Outlet Dimension(mm): | 670*670             | 670*670             |
| Applicable Area(m2):      | 100-150             | 100-150             |
| Gross weight (KG)         | 73                  | 73                  |
| 40'HQ                     | 95 pcs in SKD       | 95 pcs in SKD       |

## DLB05-DC

|                      |                     |
|----------------------|---------------------|
| Model                | DLB05-DC            |
| Airflow (m3/h)       | 5000                |
| Volt                 | 12V or 24V DC       |
| Power (W)            | 100 or 130          |
| Fan speed            | 6                   |
| Control type         | Electronic & Remote |
| Noise (db)           | ≤50                 |
| Water tank (L)       | 45                  |
| Cooler size (mm)     | 570*350*1150        |
| Gross weight (KG)    | 17.5                |
| Loading Q'ty (40 HQ) | 236                 |



## DLBW06-DC

|                      |                     |
|----------------------|---------------------|
| Model                | DLB206-DC           |
| Airflow (m3/h)       | 5000                |
| Volt                 | 12V or 24V DC       |
| Power (W)            | 100 or 130          |
| Fan speed            | 3                   |
| Control type         | Electronic & Remote |
| Noise (db)           | ≤50                 |
| Water tank (L)       | 25                  |
| Cooler size (mm)     | 640*640*700         |
| Gross weight (KG)    | 23                  |
| Loading Q'ty (40 HQ) | 215                 |



## DLB06-DC

|                      |                     |
|----------------------|---------------------|
| Model                | DLB06-DC            |
| Airflow (m3/h)       | 6000                |
| Volt                 | 12V or 24V DC       |
| Power (W)            | 100 or 130          |
| Fan speed            | 6                   |
| Control type         | Electronic & Remote |
| Noise (db)           | ≤50                 |
| Water tank (L)       | 60                  |
| Cooler size (mm)     | 720*430*1220        |
| Gross weight (KG)    | 21.7                |
| Loading Q'ty (40 HQ) | 175                 |



## DLBW08-DC

|                      |                     |
|----------------------|---------------------|
| Model                | DLBW08-DC           |
| Airflow (m3/h)       | 6000                |
| Volt                 | 12V or 24V DC       |
| Power (W)            | 100 or 130          |
| Fan speed            | 3                   |
| Control type         | Electronic & Remote |
| Noise (db)           | ≤50                 |
| Water tank (L)       | 25                  |
| Cooler size (mm)     | 830*1065*800        |
| Gross weight (KG)    | 45                  |
| Loading Q'ty (40 HQ) | 144                 |



# P2

|               |                              |
|---------------|------------------------------|
| Name          | Handy Mini Fan               |
| Material      | PP                           |
| Voltage       | DC 5V                        |
| Power         | 4.5W                         |
| Battery       | 1200mAh                      |
| N.W.:         | 123g                         |
| Dimension     | 106*210*43mm                 |
| Inner Box     | 112*212*47mm                 |
| Master Carton | 500*425*565mm                |
| Packing Qty   | 100pcs/carton                |
| Loading Qty   | 23000pcs/20FT, 56000pcs/40HQ |

1. Four colors available
2. Big airflow with 4 blades fan
3. Three speeds adjustable
4. Portable and standing available
5. Big capacity, battery 1200mAh
6. Push-button switch design, button for turn on/off, button for adjust the wind speed.



# P1

|             |                                   |
|-------------|-----------------------------------|
| Name        | Desktop USB Fan                   |
| Material    | ABS/PP                            |
| Voltage     | DC 5V                             |
| Power       | Low 2.5W/Medium 3W/High 4.1W      |
| Battery     | 1200mAh                           |
| N.W.:       | 180g                              |
| Current     | Low 535mA/Medium 615mA/High 805mA |
| Dimension   | 127*100*200mm                     |
| Loading Qty | 9440 pcs/20FT, 21600 pcs/40HQ     |

1. Three colors available
2. Big airflow with 7 blades fan
3. Three speeds adjustable
4. Easy to get an appropriate angle and 45° adjustment
5. It is ok to replace with a new usb cable
6. Built-in battery, 3 hours fast charging, last for 4 hours in low speed .

