



# OSRAM 5 FT FLORESCENT YELLOW TUBES L58/62 CHIP CONTROL

LUMILUX® CHIP control® T8 | Tubular fluorescent lamps 26 mm, with G13 bases, for UV-sensitive applications



### Product Benefits:

- Excelent UV Filter

### Product Feature :

- Excelent Filter At 500 Nm
- Long Sleeve Life (Corresponds To The Average Life Of The Lamp)
- Average Lifetime: 20,000 H With Preheat ECG

### Areas of application Areas of application

- Microchip fabrication plants
- Where UV and blue components have to be reduced to the absolute minimum
- Industry

## TECHNICAL DATA

### Electrical data

Nominal wattage	58 W
Construction wattage	58.00 W
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

### Dimensions & Weight

Overall length	1500.00 mm
Length with base excl. base pins/connection	1500 mm
Diameter	26.00 mm
Tube diameter	26 mm
Maximum diameter	26 mm
Product weight	297.00 g

### Temperatures & operating conditions

Rated ambient temp.w.max.luminous	25.0 °C
-----------------------------------	---------

### Additional product data

Base (standard designation)	G13
Mercury content	2.5 mg

**DENSBE ELECTRICAL S'pore Pte Ltd**  
403 RACE COURSE ROAD SINGAPORE 218653  
Tel: (65) 6447 3744

Email: [sales@densbe-electric.com](mailto:sales@densbe-electric.com) • Website: [www.densbe-electric.com](http://www.densbe-electric.com)