

DENSBE ELECTRICAL S'pore Pte Ltd

403 RACE COURSE ROAD SINGAPORE 218653

Tel: (65) 6447 3744

Fax: (65) 6344 1254

Email: sales@densbe-electric.com

densbe@singnet.com.sg

Website: www.densbe-electric.com



Manufactured by
vulcanization art
radiation art

Covers all spec. of rubber cable



Rubber cable, power cord, extension cord
VDE, UL, BS, GS, TUV ect.

I CABLE



POWERCORD

Application:
small and large household appliance, such as electric cooktops, ovens, toasters and heater.



Plug : European Straight Plug (IP44)
End treatment: stripping, receptacle, connector
Cable: H05RR-F 3G0.75, 3G1.0, 3G1.5, 3G2.5
H07RN-F 3G1.0, 3G1.5
IP44, 300/500V 450/750V, 16A



Plug : European Curved Plug
End treatment: stripping, receptacle, connector
Cable: H05RR-F 3G0.75, 3G1.0, 3G1.5, 3G2.5
H07RN-F 3G1.0, 3G1.5, 3G2.5
300/500V 450/750V, 16A



Plug : European Straight Plug
End treatment: stripping, receptacle, connector
Cable: H05RR-F 3G0.75, 3G1.0, 3G1.5, 3G2.5
H07RN-F 3G1.0, 3G1.5, 3G2.5
300/500V 450/750V, 16A



Plug : European Tool Plug (IP44)
End treatment: stripping, receptacle, connector
Cable: H05RR-F 2X0.75-1.5
H07RN-F 2X1.0-1.5
IP44, 300/500V 450/750V, 16A



Plug : European Tool Plug
End treatment: stripping, receptacle, connector
Cable: H05RR-F 2x0.75-1.5
H07RN-F 2x1.0-1.5
300/500V 450/750V, 16A

EXTENSION CORD

Suitable for indoor and outdoor use Application:
Construction sites, or other heavy duty operations.



Plug : European Straight Plug
End treatment: stripping, receptacle, connector
Cable: H05RR-F 3G1.0, 3G1.5, 3G2.5
H07RN-F 3G1.0, 3G1.5, 3G2.5
IP44, 300/500V 450/750V, 16A



Plug : European Straight Plug (IP44)
End treatment: stripping, receptacle, connector
Red Cable: H05RR-F 3G1.0, 3G1.5, 3G2.5
H07RN-F 3G1.0, 3G1.5, 3G2.5
IP44, 300/500V 450/750V, 16A



Plug : European Straight Plug (IP44)
Connector: one-way outlet
Cable: H05RR-F 3G1.0, 3G1.5, 3G2.5
H07RN-F 3G1.0, 3G1.5, 3G2.5
IP44, 300/500V 450/750V, 16A

Updated in 2016



Plug : European Straight Plug (IP44)
Connector: one-way outlet
Red Cable: H05RR-F 3G1.0, 3G1.5, 3G2.5
H07RN-F 3G1.0, 3G1.5, 3G2.5
IP44, 300/500V 450/750V, 16A



Plug : European Straight Plug (IP44)
Connector: one-way outlet
Yellow Cable: H05RR-F 3G1.0, 3G1.5, 3G2.5
H07RN-F 3G1.0, 3G1.5, 3G2.5
IP44, 300/500V 450/750V, 16A

■ Good flexibility & cold resistant ■ Good physical strength ■ Good acid & alkaline & oil resistance



EXTENSION CORD

Suitable for indoor and outdoor use Application:
Construction sites, or other heavy duty operations.



Plug : European Straight Plug (IP44)

Connector: two-way outlet
Cable: H05RR-F 3G1.5, 3G2.5
H07RN-F 3G1.5
IP44, 300/500V 450/750V, 16A



Plug : 3 poles CEE Plug (IP44)

Connector: 3 poles CEE Connector
Cable: H05RR-F 3G1.5
H07RN-F 3G2.5
IP44, 450/750V, 16A



Plug : 3 poles CEE Plug (IP44)

Connector: one-way outlet
Cable: H07RN-F 3G1.5, 3G2.5
IP44, 450/750V, 16A



Plug : 3 poles CEE Plug (IP44)

Connector: 3 poles CEE Connector
Cable: H07RN-F 3G1.5, 3G2.5
IP44, 450/750V, 16A, 32A



Plug : 3 poles CEE Plug (IP44)

Connector: 3 poles CEE Connector
Cable: H07RN-F 5G1.5, 3G2.5, 5G6
IP44, 450/750V, 16A, 32A

EXTENSION CORD

Suitable for indoor and outdoor use Application:
Construction sites, or other heavy duty operations.



Plug : 5 poles CEE Plug (IP67)

Connector: 5 poles CEE Connector
Cable: H07RN-F 5G16
IP67, 450/750V, 63A

***EXTENSION CORD WITH H07BQ-F CABLE**



Plug : European Straight Plug (IP44)

End treatment: stripping, receptacle, connector
Red Cable: H07BQ-F 3G1.5, 3G2.5
IP44, 300/500V 450/750V, 16A



Plug : 3 poles CEE Plug (IP44)

Connector: 3 poles CEE Connector
Cable: H07BQ-F 3G1.5, 3G2.5
IP44, 450/750V, 16A



Plug : 3 poles CEE Plug (IP67)

Connector: 3 poles CEE Connector
Cable: H07RN-F 5G16
IP67, 450/750V, 63A

■ Good flexibility & cold resistant ■ Good physical strength ■ Good acid & alkaline & oil resistance



CABLE REEL

Suitable for universe outdoor use.

*Large quantity sold to top European cable reel manufacturers on OEM basis.



Plug : European Straight Plug (IP44)

Connector: three-way outlet

Cable: H05RR-F 3G1.5, 3G2.5
H07RN-F 3G1.5, 3G2.5



Plug : European Straight Plug (IP44)

Connector: three-way outlet

Cable: H05RR-F 3G1.5, 3G2.5 (Yellow)
H07RN-F 3G1.5, 3G2.5 (Yellow)



Plug : European Straight Plug (IP44)

Connector: one-way outlet

Cable: H05RR-F 3G1.5, 3G2.5 (Red)
H07RN-F 3G1.5, 3G2.5 (Red)



Plug : CEE 3pole Plug (IP44)

Connector: CEE 3pole

Cable: H07RN-F 3G1.5, 3G2.5



Plug : CEE 5pole Plug (IP44)

Connector: CEE 5pole

Cable: H07RN-F 5G1.5, 5G2.5

CABLE RING

Used for power cord, extension cable, cable reel, connecting cable, service such as stripping is available.



Color:black

Cable Ring

Cable: H05RR-F 3G1.5, 3G2.5
H07RN-F 3G1.5, 3G2.5
H07RN-F 5G1.6, 5G2.5, 5G4, 5G6, 5G16

Rate voltage: 300/500V, 450/750V

Length: 5m----50m



Color:red

Cable Ring

Cable: H05RR-F 3G1.5, 3G2.5
H07RN-F 3G1.5, 3G2.5
H07RN-F 5G1.6, 5G2.5, 5G4, 5G6, 5G16

Rate voltage: 300/500V, 450/750V

Length: 5m----50m



Color:yellow

Cable Ring

Cable: H05RR-F 3G1.5, 3G2.5
H07RN-F 3G1.5, 3G2.5
H07RN-F 5G1.6, 5G2.5, 5G4, 5G6, 5G16

Rate voltage: 300/500V, 450/750V

Length: 5m----50m



Color:white

Cable Ring

Cable: H05RR-F 3G1.5, 3G2.5
H07RN-F 3G1.5, 3G2.5
H07RN-F 5G1.6, 5G2.5, 5G4, 5G6, 5G16

Rate voltage: 300/500V, 450/750V

Length: 5m----50m



Color:orange

Cable Ring

Cable: H05RR-F 3G1.5, 3G2.5
H07RN-F 3G1.5, 3G2.5
H07RN-F 5G1.6, 5G2.5, 5G4, 5G6, 5G16


Rate voltage: 300/500V, 450/750V

Length: 5m----50m

■ Good flexibility & cold resisitant ■ Good physical strength ■ Good acid & alkaline & oil resistance



WHY CHOOSE US


 Durabile, long life service, produced by vulcanization/ radiation with environment friendly material


 Oil, Acid, Alkali, UV resistant


 Reach/Rohs compliant

 Excellent mechanical strength

Unknown brands:

 Unable to work in frequently over bent/dragged/robust conditions

 Unable to work in harsh environment

 Contain harmful materials SVHC, PFOA, PFOS, PAHS, Pb, Cr

 Unable to work in frequently over bent/dragged conditions




 Symmetrical structure




 High voltage test: PASS




 Physical strength/elongation test: PASS



 -35C°/-40C° test: PASS



 Large crimping area, connection of cable with plug keeps intact in dynamic use

Unknown brands:




 Non-symmetrical structure



 High voltage test: NOT PASS




 Physical strength/elongation test: NOT PASS



 -35C°/-40C° test: NOT PASS



 Narrow/cutting crimping connection of cable and plug makes it easily broken in dynamic use

rubber cable VDE,UL,CCC certified

 Oxygen free, refined copper 99.9%, energy saving

 Inferior copper, containing foreign materials, even with bigger cross section, but fail in electric resistant test

 Safe to operate in hot environment

 Easily get on fire when overheating, give off hazardous gas

 Electric resistant test: PASS

 Electric resistant test: NOT PASS

 More flexible, cold-resistant;

 Good physical strength;

 Rigid connection ensures reliability during dynamic use

